




# BTE 13

## BEHIND-THE-EAR

**Livio Edge AI 1200 | 1000**  
**Livio AI 1200 | 1000**  
**Livio 1200 | 1000**

### Color Guide




### Accessory Compatibility

- TV
- Remote Microphone +
- Remote
- Mini Remote Microphone
- Table Microphone
- 2.4 GHz Programmer

### Fitting Range

● BTE 13 70



### Patient Features

- Tinnitus Technology
- Telecoil
- Wireless Connectivity
- CROS System\*\*



### Livio Edge AI/ Livio AI Technology

- Healthable hearing technology with embedded sensors and artificial intelligence

Measurement	Earhook		Size 3, Occluded Thin Tube	
	ANSI/IEC 2cc Coupler	IEC OES Coupler	ANSI/IEC 2cc Coupler	IEC OES Coupler
Peak OSPL90 (dB SPL)	130	136	124	129
HFA OSPL90 (dB SPL)	122	N/A	112	N/A
RTF OSPL90 (dB SPL)	N/A	134	N/A	114
Peak Gain (dB)	70	76	68	73
HFA Full-On Gain (dB)	62	N/A	57	N/A
RTF Full-On Gain (dB)	N/A	73	N/A	61
<b>Frequency Range (Hz)</b>	<100-7600	<100-7600	<100-4600	<100-6800
Reference Test Freq. (kHz)	N/A	1.6	N/A	1.6
HFA Frequencies (kHz)	1.0,1.6,2.5	N/A	1.0,1.6,2.5	N/A
Reference Test Gain (dB)	45	59	35	39
Equivalent Input Noise (dB)	24	18	29	29
<b>Harmonic Distortion</b>				
500 Hz (%)	<3	<3	<3	<3
800 Hz (%)	<5	<5	<3	<3
1600 Hz (%)	<2	<2	<2	<2
<b>Induction Coil Sensitivity</b>				
HFA SPLITS (ANSI) (dB SPL)	101	N/A	91	N/A
MASL (IEC) (dB SPL)	92	N/A	88	N/A
ANSI/IEC Battery Current (mA)	1.9*	1.8*	1.9*	1.8*
Idle Current (mA)	1.7*	1.7*	1.7*	1.7*
<b>Estimated Battery Life for 16-Hour Day</b>				
13 Zinc Air (days)	7-11*	7-11*	7-11*	7-11*
<b>Tinnitus Therapy Stimulus</b>				
Max RMS Output (dB SPL)	87		87	
Weighted RMS Output Level (dB SPL)	87		87	
Max 1/3 Octave Output (dB SPL)	87		87	

▶ Matrices: 130/70

▶ Battery Size: 13



All Technical Data in accordance to ANSI S3.22-2014 and IEC 6018-0:2015 using 2cc Coupler

\*Results will vary based on wireless usage.

\*\*Only available on 1200 technology tier.

Livio and Healthable are trademarks of Starkey Laboratories, Inc.  
 © 2019 Starkey. All Rights Reserved. 12/19 SPEC2813-03-EE-ST